CARDIOVIT AT-1

Bet on this 3-channel ECG by SCHILLER!

The CARDIOVIT AT-1 performs quick and accurate 12-lead ECG analysis, in a three channel format, at a price for one-channel systems.

With its compact, easy-to-use operation and built-in battery, the AT-1 is perfect for all applications including stationary office use, hospital bedsides and ambulatory field work. Reliable, powerful and low-maintenance, the AT-1 is the ideal cost-effective ECG unit for professional electrocardiography.

Over 100'000 units have been sold worldwide!



- Simultaneous 12-lead acquisition
- 3-channel print format
- One-button operation
- Multiple report formats
- Copy functions
- Various recording rates
- Automatic and manual modes
- Built-in thermal printer
- Built-in, rechargeable battery
- Built-in charger unit
- Lightweight (2,9 kg/6.7 lbs)

Options:

- Measurement software
- Interpretation software





Technical Data AT-1:

Dimensions: 290 x 210 x 69 mm / 11.4 x 8.3 x 2.7 in. (I/w/h)

Weight: Ca. 2.9 kg / approx. 6.7 lbs

Power supply requirements: 220 – 240 V (nominal), 50/60 Hz or 110 – 115 V (nominal), 50/60 Hz independent operation with built-in rechargeable battery, LED indicator for mains and battery, built-in charger unit

Power consumption: Max. 28 VA

Battery charging time: 15 hrs. from a completely discharged battery,

3 hrs.to 60 % capacity

Battery capacity: 2 hrs of normal use

Leads: Standard / Cabrera

Patient input circuitry: Fully floating and isolated, defibrillation protected (only with original SCHILLER patient cable)

Frequency range of digital recorder: 0 Hz to > 150 Hz (IEC/AHA)

ECG amplifier:

- Simultaneous, synchronous registration of all 9 active electrode signals (= 12 standard leads)
- Sampling frequency: 1000 Hz
- Pacemaker detection: $\geq \pm 2 \text{ mV/} \geq \pm 0.1 \text{ ms}$

Myogram (muscle tremor) filter:

25 Hz (40 dB/dec) or 35 Hz (20 dB/dec), programmable

Line frequency filter: Distortion-free suppression of superimposed 50 or 60 Hz sinusoidal interferences by means of an adaptive digital filter

Control panel: Pad keys, LED indicators

LED indicators:

- Lead group
- Paper tray empty or jammed
- Mains connected - Filter status (on/off) - Battery operation and battery
 - Loose electrodes

low (indicator flashes)

Norms:

Safety Standards: IEC/EN 60601-1; UL 60601-1; C22.2 No. 601.1-M90; IEC/EN 60601-2-25; IEC/EN 60601-1-2 (EMC)

Protection Class: I according to IEC/EN 60601-1 (with internal power

Applied Part: CF according IEC/EN 60601-1

Conformity: according Directive 93/42/EEC (Medical Devices)

Classification: Ila according Directive 93/92/EEC

Environmental conditions:

- Temperature, operating: 10° to 40° C / 50° to 104° F
- Temperature, storage: -10° to 50° C / 14° to 122° F
- Relative humidity: 25 to 95 % (non-condensing)
- Pressure, operating: 700 1060 hPa

Printing (built-in thermal printer):

Paper speed: 5 / 25 / 50 mm/s (direct)

Sensitivity: 5 / 10 / 20 mm/mV, either automatically adjusted or manually selected

Chart paper: Thermoreactive, Z-folded, 90 mm / 3.5 in wide, or Roll, 90 mm wide

Printing process:

High-resolution thermal printhead

8 dots per mm / 200 dots per in (amplitude axes)

40 dots per mm / 1000 dots per in (time axes, @ 25 mm/s)

Recording tracks: 3 channels, positioned at optimal with on 80 mm / 3.2 in., automatic baseline adjustment

Automatic lead programs:

3 channel representation of 12 simultaneously acquired standard leads

Data record:

 With option M: ECG measurement results (intervals, amplitudes, electrical axes, average complexes with optional measurement reference markings)

CARDIOVIT AT-1 basic unit with 3-channel Resting ECG with 12 simultaneous leads and pacemaker detection

Accessories

- 10-lead patient cable
- 1 set of electrodes, consists of 4 stainless steel extremity electrodes, 6 precodial electrodes or disposable electrodes
- Electrode gel
- Power cable
- 1 pkg. of recording paper
- Operating manual
- Cart (optional)

Software-Options:

Automatic measurement and interpretation program for resting ECGs

Technical data are subject to change without notice.

Your specialist:

SCHILLER Asia-Pacific

52200 Kuala Lumpur, Malaysia Phone +603 6272 3033 sales@schiller.com.my

www.schiller-asia.com

Austria SCHILLER Handelsgesellschaft mbH

A-4040 Linz Phone +43 732 70 99-0 sales@schiller.at www.schiller-austria.com

China SCHILLER International Trading

Co. Ltd. 200335 Shanghai, China Phone +8621 6209 9627 sales@schiller.com.my www.schiller.cn

France

SCHILLER Médical S.A.S. F-67162 Wissembourg/Cedex Phone +33 3 88 63 36 00 info@schiller.fr www.schiller-france.com

France (bureau Paris) SCHILLER France S.A.S.

F-77608 Bussy-Saint-Geor Phone +33 1 64 66 50 00 info@schillerfrance.fr www.schiller-france.com

Germany SCHILLER Medizintechnik GmbH

D-85521 Ottobrunn Phone +49 89 62 99 81-0 info@schillermed.de www.schiller-germany.com

Hungary SCHILLER Diamed Ltd. H-1141 Budapest Phone +36 (1)460 05 92 sales@t-online.hu www.schiller-hungary.hu

SCHILLER Healthcare India Pvt. Ltd. Mumbai - 400 059, India Phone +91 222 2826 35 20 sales@schillerindia.com www.schillerindia.com

Japan SCHILLER Japan, Ltd. Hiroshima 734-8551 Phone +81 82 250 2055 koji.maekawa@schiller.jp www.schiller.jp

Poland SCHILLER Poland Sp. z o.o. PL-02-729 Warszawa

Phone +48 22 843 2089 schiller@schiller.pl www.schiller.pl

Russia & C.I.S

SCHILLER AG

125124 Moscow, Russia Phone +7 (495) 970 11 33 mail@schiller-ag.com www.schiller-cis.com

Spain SCHILLER ESPAÑA, S.A.

E-28230 Las Rozas/Madrid Phone +34 91 713 01 76 schiller@schiller.es www.schiller-spain.com

Switzerland SCHILLER-Reomed AG CH-8953 Dietikon Phone +41 44 744 30 00 sales@schiller-reomed.ch www.schiller-reomed.com

Turkey

SCHILLER TÜRKIYE
Okmeydani-Sisli – Istanbul
Phone +90 212 210 8681 (pbx)
sales@schiller-turkiye.com www.schiller-turkive.com

SCHILLER America Inc. Doral, Florida 33122

Phone +1 786 845 0620 sales@schilleramerica.com www.schilleramerica.com



